

FEATURE:


- Frequency Range : 2400 MHz ~ 2700 MHz
- SIZE: 12.7×12.7×5.0 mm ;
- ROHS ;

ELECTRICAL SPECIFICATION


Frequency Range		2400 MHz ~ 2700 MHz
Tuning voltage	V _{DC}	1.0 ~ 8.0
Tuning Sensitivity	MHz/V	60±15
Phase Noise	dBc/Hz @offset	≤-92 @ 10KHz ; ≤-110 @ 100KHz
Output Power	dBm	8±2
Pushing	MHz	±2.5
Pulling (1.67:1 VSWR)	MHz	10
Supply Voltage	V _{DC}	5.0±0.25
Supply Current	mA	40
Harmonic 2nd	dBc	-15
Input Capacitance	pF	20
Operating Temperature	°C	-40°C ~ +85°C

OUTLINE DRAWING (mm)

BOTTOM VIEW




TOP VIEW



PIN OUT FOR VCO	
	PIN
OUTPUT	10
Vcc	14
Vt	2
GND	OTHERS



SIDE VIEW



RECOMMENDED LAND PATTERN (TOP VIEW)

SYMBOL	DIMENSION
	MILLIMETERS
A	12.7±0.2
B	12.7±0.2
C	4.7 MAX
E	8.0±0.1
F	7.15±0.1
G	5.5±0.1
H	1.7±0.1
J	0.8±0.1
K	3.6±0.1
L	1.5±0.1
M	2.54±0.08